

WTRVS-8/15 Series Voice Reach Talking Pendant Necklace



WTRVS-8/15 is a small and lightweight Voice Reach Talking Pendant. Compact and easy-to-use, WTRVS-8/15 is designed to provide complete protection anywhere around your home at any time with the simple touch of a button.

WTRVS-8/15 allows immediate post-alarm voice follow up after an emergency call without any delay and effort. With a simple press of a button it can open two-way voice communication channel between you and the Central Monitoring Station. Additionally, users can talk to the Central Monitoring Station right through the pendant like a speaker phone with the built-in microphone and speaker.

WTRVS-8-FS and WTRVS-15-FS also has a built-in fall sensor and will automatically raise an alarm call and activates two-way voice communications when falls have been detected. As an intelligent device, WTRVS-8/15 really ensures that your emergency issue can be handled properly and timely.



- Raises a alarm call when a fall as been detected (WTRVS-8-FS & WTRVS-15-FS only)
- The microphone and speaker inside allow users to talk to the Central Monitoring Station like a speaker phone
- Immediate post-alarm voice follow up after an emergency call
- Waterproof to IP67
- Power-saving feature for Panel (WTRVS-15 & WTRVS-15-FS only)
- Compact and easy to use
- Worn around the neck as a pendant
- Compatible with Climax Medical Alarm Panels

WTRVS-8/15 Series Voice Reach Talking Pendant Necklace

Comprehensive Protection at Home

Specifications

WTRVS-8

| | |
|-----------------------|---|
| DECT Frequencies | 1880MHz-1900MHz (EU) / 1910MHz – 1930MHz (US) |
| Power Source | 3V, CR123A Lithium battery x1 |
| Battery Life | 2.8 years* |
| Waterproof Standard | IP67 |
| Operating Temperature | -10°C to 45°C (14°F to 113°F) |
| Operating Humidity | Up to 85% non-condensing |
| Dimensions | Ø 60mm x 24mm |

WTRVS-8-FS

| | |
|-----------------------|---|
| DECT Frequencies | 1880MHz-1900MHz (EU) / 1910MHz – 1930MHz (US) |
| Power Source | 3V, CR123A Lithium battery x1 |
| Battery Life | 1.5 years* |
| Waterproof Standard | IP67 |
| Operating Temperature | -10°C to 45°C (14°F to 113°F) |
| Operating Humidity | Up to 85% non-condensing |
| Dimensions | Ø 60mm x 24mm |

WTRVS-15

| | |
|-----------------------|---|
| DECT Frequencies | 1880MHz-1900MHz (EU) / 1910MHz – 1930MHz (US) |
| RF Frequencies | F1 869MHz / 433MHz |
| Power Source | 3V, CR123A Lithium battery x1 |
| Battery Life | 3 years* |
| Waterproof Standard | IP67 |
| Operating Temperature | -10°C to 45°C (14°F to 113°F) |
| Operating Humidity | Up to 85% non-condensing |
| Dimensions | Ø 60mm x 24mm |

WTRVS-15-FS

| | |
|-----------------------|---|
| DECT Frequencies | 1880MHz-1900MHz (EU) / 1910MHz – 1930MHz (US) |
| RF Frequencies | F1 869MHz / 433MHz |
| Power Source | 3V, CR123A Lithium battery x1 |
| Battery Life | 1.58 years* |
| Waterproof Standard | IP67 |
| Operating Temperature | -10°C to 45°C (14°F to 113°F) |
| Operating Humidity | Up to 85% non-condensing |
| Dimensions | Ø 60mm x 24mm |

* Note: Actual battery life may vary with product settings, operating environment, and usage.

WTRVS-8/15 Series Voice Reach Talking Pendant Necklace

Comprehensive Protection at Home

Ordering Information

| | |
|-------------|---|
| WTRVS-8 | Voice Reach Talking Pendant Necklace |
| WTRVS-8-FS | Voice Reach Talking Pendant Necklace with Fall Detection |
| WTRVS-15 | Voice Reach Talking Pendant Necklace with power-saving feature |
| WTRVS-15-FS | Voice Reach Talking Pendant Necklace with Fall Detection & power-saving feature |



Grey



Red



Blue

**We offer multiple color options to fulfill all user's needs. Please inquire our Sales team for color options.